

CHARACTER:

1.Physical performance

- a、Good mechanical properties
- b、Good resistance to high temperature, low temperature resistance
- c、Good flame retardancy
- d、Good corrosion resistance
- e、Good resistance to climate
- f、Good lubricity (small friction coefficient)
- g、Excellent resistance to radiation
- h、Good resistance to twists
- i、Good resistance to cracking

2.Electrical Properties

- a、Electrical insulation good
- b、Has the very high resistivity

3.Processing properties

- a、Use half extrusion processing
- b、Good wire processing performance
- c、In the process of wire processing good compatibility
- d、According to UL standard design

4.Environmental protection

- a、ROHS/REACH compliant
- b、nonhazardous

SHOULD BE USED:

Internal wiring of appliances or electronic equipment.

REFERENCE:

UL758-2010、UL1581-2009

Outline:

Strands Nickel /silver/bare copper conductor



PFA Insulation

Internal wiring of appliances or electronic equipment. UL10485

Wire structure description:
Conductor: Nickel /silver/bare copper conductor;
Insulation materials: PFA Insulation

Conductor temperature not over 250℃ PFA insulated wire								
Rated temperature: 250℃ rated voltage: 600V								
STYLE	standard AWG	Conductor size (No./ mm) ±0.005mm	Conductor resistance 20℃ (Ω/Km)	Conductor Dia.(mm)	insulation thickness (mm)		Overall diameter (mm)	
					Nom.	Min.	Mon	Tol
10485	20	7/0.3	36.70	0.92	0.20	0.15	1.36	±0.10
	22	19/0.15	59.40	0.76	0.20	0.15	1.15	±0.10
	24	7/0.20	94.20	0.61	0.20	0.15	1.00	±0.10
	26	7/0.16	150.00	0.49	0.20	0.15	0.88	±0.10
	28	1/0.32	227.00	0.32	0.20	0.15	0.72	±0.10
	28	7/0.127	227.00	0.39	0.20	0.15	0.72	±0.10
	30	1/0.254	361.00	0.254	0.20	0.15	0.66	±0.10

Marking: E211048 AWM STYLE 10485 NO.AWG 250℃ 600V VW-1 PFA QIFURUI-LF-

SAE COLOR SERIES

* STOCK COLOR CHART				
00-BLACK	01-WHITE	02-RED	03-YELLOW	04-GREEN
05-BLUE	06-BROWN	07-GREY	08-ORANGE	09- VIOLET

PACKAGE

*PACKAGE				
Part No.	Packing- FT/roll			
10AWG	☒ 500Ft	☐ 1000Ft	☐ 2000Ft	
12~20AWG	☐ 500Ft	☒ 1000Ft	☐ 2000Ft	
22-30AWG	☐ 500Ft	☐ 1000Ft	☒ 2000Ft	
According to customer requirements for packaging packaging				